

# ADSL PCI Modem

## Advantage Series

## Technical Specifications

### Chipset

Conexant

### ADSL Standard Compliance

G.992.1 (Full Rate DMT over Analog POTs)

G.992.2 (G.lite)

ANSI T1 413 Issue 2

### Protocol Support

RFC-2364 PPP over ATM

RFC-1483 Multi-Protocol Encapsulation over ATM

RFC-2516 PPP over Ethernet

### Line Speed

G.lite Mode:

Downstream up to 1.5Mbps/Upstream up to 512Kbps

G.dmt Full Rate Mode:

Downstream up to 8Mbps/Upstream up to 1Mbps

### System Requirement

Operating System Support: Win 98/98SE/ME/2000

Pentium Class 166MHz/64RAM/USB Port

### Environment

Operating Temperature: 0° C- 40° C

Non-Operating temperature: -40° C- 85° C

Humidity: 5% to 90% (non-condensing)

### Ordering Information

WTM2100: PCI Modem



### Loop Range

Up to 18,000 feet

### Interface

ADSL: RJ-11 Connection

Analog Phone: RJ-11 Connection

### LED Indicator

ACT/Link

### Physical Dimension

130mm x 80mm (5.1 x 3.1 in)



3731 Wilshire Blvd. Suite 506, Los Angeles, CA 90010. Tel: 213-380-7555, Fax: 213-380-1736.

<http://www.wtcelectronics.com>. Email: [sales@wtcelectronics.com](mailto:sales@wtcelectronics.com)