

ADSL USB Modem Advantage Series

Technical Specifications

ADSL Standard Compliance

G.992.1 (Full Rate DMT over Analog POTs)
G.992.2 (G.lite)
ANSI T1 413 Issue 2

Protocol Support

RFC-2364 PPP over ATM
RFC-1483 Bridged over Ethernet over ATM
RFC-1483 Multi-Protocol Encapsulation over ATM
RFC-2516 PPP over Ethernet

Line Speed

G.lite Mode:
Downstream up to 1.5Mbps/Upstream up to 512Kbps
G.dmt Full Rate Mode:
Downstream up to 8Mbps/Upstream up to 1Mbps

System Requirement

Operating System Support: Win 98/98SE/ME/2000
Pentium Class 166MHz/64RAM/USB Port

Physical Dimension

135mm(L) x 36mm(W) x 110mm(H)

Ordering Information

WTM3150: USB Modem, Globespan chip.



Interface

USB: Compliant with USB Specification, Rev 1.1
ADSL: RJ-11 Connection

Loop Range

Up to 18,000 feet

LED Indicator

Power/ACT/Link

Power

Bus Powered USB
Tone detection for low power mode

Environment

Operating Temperature: 0° C- 40° C
Non-Operating temperature: -40° C- 85° C
Humidity: 5% to 90% (non-condensing)



3731 Wilshire Blvd. Suite 506, Los Angeles, CA 90010. Tel: 213-380-7555, Fax: 213-380-1736.
<http://www.wtcelectronics.com>. Email: sales@wtcelectronics.com